



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension							
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet		
								E	F	d	E	F	d
20A(C)4,5Y006	4,5	6,14	14,33	250	3500	42,5	80						
20A(C)6,3Y006	6,3	8,69	20,29	250	3500	42,5	80	30,2	13,1	M6-6H		13,1	
20A(C)8,2Y006	8,2	11,32	26,40	250	3500	42,5	80						
20A(C)10Y006	10	13,95	32,55	250	3500	47	89						
20A(C)11Y006	11,3	15,76	36,78	250	3500	48	91,1						
20A(C)12Y006	12	16,92	39,48	250	3500	48,6	92,3						
20A(C)14Y006	14	19,95	46,55	250	3500	50	95,4						
20A(C)15Y006	15	21,60	36,00	250	2500	51	96,9	39,7	19	M8-6H	30,2	14,2	M6-6H
20A(C)16Y006	16	23,04	38,40	250	2500	52	98,6						
20A(C)19Y006	19	27,36	45,60	200	2500	54	103,5						
20A(C)22Y006	22	31,68	42,24	180	2000	57	108,5						
20A(C)25Y006	25	36,00	48,00	160	2000	59,2	113,4				39,7	19	M8